

M20 SE


Mobile Terminal



Upgrade your experience with a combination of speed, convenience and portability

- Versatile mobile terminal powered by Android 13 for all mobile business needs.
- Supported by LANDI's asset management platform, **LANDI Connect**, to meet the evolving demands of today's digital world.
- Pocket-size design, enabling high-level productivity and connectivity on the go.

- Expansive 6.5" touch screen and ergonomic interface
- Powerful processor for smooth operation
(Qualcomm Quad-core, 2.0GHz)
- Quick-swap battery on duty(3500mAh/7.7V)
- Advanced connectivity for high-mobility(2G/3G/4G, WiFi, GPS, Bluetooth 5.0)
- 5MP rear camera for convenient QR code reading
Optional front camera



| SPECIFICATIONS

Processor	Qualcomm Quad-core, 2.0GHz	Positioning	GPS, GLONASS, BEIDOU
OS	Android 13 (GMS Certified)	Camera	Front camera: optional, 2M pixels, fixed focus camera, for code scanning Rear camera: 5M pixels, autofocus and flashlight
Memory	3GB RAM+32GB FLASH 4GB RAM+64GB FLASH (Optional) 2GB RAM + 16GB FLASH (Optional, No GMS) Micro SD Card (Up to 2TB)	NFC (Optional)	Android NFC, ISO/IEC 14443, ISO15693 compliant, support Type A/B, Mifare, Felica
Display & Touchscreen	6.5", IPS, 720x1600 HD capacitive multi-touch	SIM/SAM Slots	· 2 SIM + 2 SAM
Scanner	· Option 1: None · Option 2: LANDI Scan Engine · Option 3: Honeywell Scan Engine	Connection	· 1 USB Type-C · 2 PIN Pogo Pin
Buttons	1 power key (Right side) 2 scan code keys are located on each side (Optional) 2 volume keys (Left side)	PSU	5V/2A
Audio	Speaker: 1W 90dB@0.1m Headset: USB Type-C MIC: Dual MIC	Battery	3500mAh/7.2V, removable
Connectivity	Cellular: 4G fallback 3G and GPRS, Global band Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4G and 5G Bluetooth: Bluetooth 5.0, support BLE	Size	L-17cm W-8cm H-2cm 6.69" x 3.15" x 0.79"
Protection	1.2m drop tested *Data from LANDI lab	Accessories (Optional)	· Terminal charging base; · Battery charger (Support 4 batteries) · Hand strap
Sensor	· G-sensor, support screen rotation automatic · Light Sensor	Environment	Operating temperature: -10°C to +50°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non- condensing
		Certifications	CE/CB/FCC/IC/RoHS/WEEE/GMS

*When MicroSD card is inserted. Card slot is 1 SIM + 1 MicroSD + 2 SAM.

LANDI

LANDI reserves the right to modify or update any information provided herein without prior notice, including the design, construction, materials, processing, or specifications of any products. Additionally, LANDI may discontinue or restrict the production or distribution of any products.

