

Lector de código de barras

IS-300Wn

10
pos



Códigos 1D & 2D



Características

Mecanismo	Imager CMOS 2D
Resolución	640*480
Fuente de luz	Aimer Led Blanco 617 nm
Método de uso	Manual o sobremesa. Lectura automática o con pulsador.
Simbologías	1D: EAN, UPC, Code 39, Code 93, Code 128, Codabar, UCC/EAN-128, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 DataBar, GS1 Composite Code, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5. 2D: QR Code, Data Matrix, PDF417, Micor PDF417, Aztec, Hanxin.
Distancia lectura	25 ~ 300 mm (QR Code)
Resistencia	Soporta caídas a 1.5m
Interface	Wireless hasta 10m. Dongle USB.
Color	Negro
Soporte	Incluido
Peso	165g (sin soporte)
Medidas	102 * 71 * 177 mm (sin soporte)
Temp. trabajo	-20 - 50°C
Temp. almacén	-40 - 70°C
Humedad	5% a 95% (No condensada)
Voltaje	+5V +/- 5%
Consumo	280 mA (en Stand By: 60mA)
Capacidad Batería	1400 mA



Con soporte



www.10pos.es